



# Interior Zone Protectors SAP1 and SAP6T2V1

## Features and Benefits

- UL listed surge protection
- Rated for 120VAC 15A, grounded outlets
- Easy Installation by homeowner for individual or multiple appliances
- Visual indication of "Protected" status
- Multiple outlet taps have mounting screw
- Lifetime product warranty
- Lifetime \$100,000 connected equipment warranty when all 3 surgeassure™ Main Zone Protectors are installed

The surgeassure™ SAP1, and SAP6T2V1 space saving wall plug protectors are designed for applications where a plug strip is not practical.

The SAP1 is ideal for answering machines, fax machines, and any 120 volt appliance such as refrigerators, washing machines, microwave ovens, and garage door openers.

surgeassure™  
14550 58th Street North Clearwater, Florida 33760  
1.800.727.0669 - info@surgeassure.com - www.surgeassure.com



The SAP6T2V1 is ideal for protecting TV's, computers, and any electronic equipment where multiple outlets and a low profile are preferable.

Major household electrical and electronic equipment are covered against surge damage for Lifetime during ownership by the original purchaser when a surgeassure™ Wall Plug Interior Zone Protector is installed and when surgeassure™ Main Zone Protectors are installed.

If the interior zone surge protector is damaged during the warranty period surgeassure™ will replace it free of charge!

# Technical Specifications

C Surge Protection	SAP1	SAP6T2V1
Surge Capacity	36,000 A	15,000 A
Line Voltage	120VAC	120VAC
Protected AC Outlets	1	6
Phone Lines Protected	N/A	1 In, 2 Out
Coax Line Protected	N/A	1
Patch Cord Provided	N/A	Yes

Agency Approvals & Warranty	
UL Listings	1449 TVSS, UL 498, UL 497A
UL 1449 Rating	330V
Product Warranty	Lifetime
*Connected Equipment Warranty	Lifetime

\*Requires all 3 surgeassure™ Main Zone Protectors to be installed at the homes incoming service.



## Selection Information

### Wall Plug Interior Zone Protectors

Catalog Number	Description
SAP1	1 Outlet Wall Plug
SAP6T2V1	6 Outlet Wall Plug with 1 Phone IN, 2 OUT, 1 Coax

### Installation:

1. If the surgeassure™ protector has a mounting screw, remove the center screw of the receptacle.
2. Plug the protector into the receptacle and secure with the mounting screw.
3. If the protector is equipped with telephone protection, use the supplied telephone extension cord to connect the telephone line from the input jack of the protector to the wall jack.
4. Connect the equipment to the output jack of the protector using the existing telephone cord.
5. Connect the equipment cord(s) into the AC receptacles of the protector.
6. If the protector has coax cable protection, connect cable from signal source to the input jack of the protector and cable from the output jack of the protector to the TV or other protected equipment.

For More Information Contact:

surgeassure™  
 14550 58th Street North Clearwater, Florida 33760  
 1.800.727.0669 - info@surgeassure.com - www.surgeassure.com